

Wild Street Diesel 4x4 Rules

(All general rules apply)

8500 pound class

- 8500 pound maximum weight with driver
- No hanging weight
- Weight securely mounted in the bed is permitted
- Vehicle must be on the road with current insurance, registration, and inspection for the state in which it is registered
- Body and Chassis must be OEM to vehicle retaining all factory body panels
- Aftermarket hoods are permitted
- OEM firewalls and floor pans are required and must not have any additional holes
- Must retain a full interior with OEM airbags
- Drivetrain must be from a similar year, make, and model one ton or less
- Cooling system must be in its factory location
- Electric fans and water pumps are permitted
- Coolant must flow freely through the block
- No fillers in the block
- No turbocharger(s) restriction
- Turbocharger may be relocated
- Intercooler may be relocated or aftermarket (air to air only)
- Any exhaust is allowed but all exhausts must air upwards
- PPL-approved billet turbine cage and Kevlar blanket required
- Injectables are prohibited
- 35x12.50 maximum tire size
- DOT approved tires only
- No cut, studs, chains, or altered tires
- No dual wheels
- 24" maximum hitch height
- Front suspension must be OEM style
- Strut lower braces, lower tie straps, sway bars, limiting straps, and ladder bars are permitted
- Rear suspension must be OEM style
- Must have 2 shocks minimum